Product Specifications For CB2.7 GC



Weights

Standard Operating Weight with ROPS	2698 kg
Maximum Operating Weight with ROPS	3198 kg
Maximum Weight at Rear Drum	1398 kg
Maximum Weight at Front Drum	1301 kg

Dimensions

Compaction Width	1200 mm
Drum Diameter	720 mm
Drum Width	1200 mm
Height - ROPS	2595 mm
Overall Length	2596 mm
Overall Width	1312 mm
Wheel Base	1800 mm

Operating Specifications

Curb Clearance	453 mm
Drum Offset	50 mm
Ground Clearance	285 mm
Static Linear Load	11.85 kg/cm
Travel Speed - Maximum	9.4 km/h

Turning Radius - Inside Drum Edge	2540 mm
Turning Radius - Outside Drum Edge	3740 mm

Engine

Gross Power	18.4 kW
Engine Model	C1.7T
Net Power - ISO 9249	18.2 kW

Vibratory System

Centrifugal Force - Maximum	31 kN
Nominal Amplitude - High	0.52 mm

Service Refill Capacities

Water Spray Tank Capacity	200
Fuel Tank Capacity	55 I

CB2.7 GC Standard Equipment

OPERATOR ENVIRONMENT

Adjustable Suspension Seat with Operator Presense Switch
ROPS Folding
Seat Belt - 75 mm (3 in) high visibility orange
Operator Console w/ Water Tank Gauge, Emergency Stop, and Glove Box
12-volt Power Outlet
Horn, Backup Alarm

COMPACTON SYSTEM

Folding Scrapers
Vibe Selection - front, rear, or both
Pressurized, Triple-Filtration Spray System with Test Mode

POWERTRAIN

Auto Engine Off and Auto Warmup Air Cleaner, Dual Element

TECHNOLOGY

Telematics

ELECTRICAL

LED Working Lights

OTHER

Vandal Protection - lockable hood, fuel fill, and controls cover Machine Life and Tiedowns Offsets Hitch

CB2.7 GC Optional Equipment

OPERATOR ENVIRONMENT

ROPS Fixed Sun Canopy Seat - Side Shift Dual Propel Levers

COMPACTON SYSTEM

Fixed Scrapers
Cocoa Mats
Edge Cutter Ready
Water Sprayer Antifreeze Kit
Ballast Kit - 200 kg (440 lb)
Ballast Kit - 400 kg (880 lb)

POWERTRAIN

Traction Control

TECHNOLOGY

Remote Flash / Troubleshoot CMV - Compaction Measurement Value

ELECTRICAL

Battery Disconnect LED Roading Lights Rotating Amber Beacon

OTHER

Biodegradeable Hydraulic Oil

Bumpers Single Point Lift Custom Paint